



BULLPRO


NEW ARRIVAL



1430 lm, 12 W.



2650 lm, 24 W.




2750 lm, 24 W.

Input voltage	9-32 V DC	9-32 V DC	9-32 V DC
Power consumption	0.89 A @ 13,7 V	1.67 A @ 13,7 V	1.73 A @ 13,7 V
LED	6 x Osram LED	16 x Osram LED	16 x Osram LED
Lumens (theor. / tested)	1600 lm / 1430 lm	3000 lm / 2650 lm	3100 lm / 2750 lm
Color temperature	5000 K	5000 K	5000 K
IP rating	IP69K	IP68	IP68
Cable / connection	Integrated DT-plug downward	Integrated DT-plug downward	Integrated DT-plug downward
Size (W x H x D)	153 x 38 x 49 mm	70 x 68 x 41 mm	70 x 70 x 41 mm
Approvals	R23, R10	R23, R10	R23, R10


1603-300235

1603-300230


1603-300231



6020 lm, 54 W.



6050 lm, 54 W.



9240 lm, 96 W.

Input voltage	9-32 V DC	9-32 V DC	9-32 V DC
Power consumption	3.60 A @ 13,7 V	3.89 A @ 13,7 V	6.03 A @ 13,7 V
LED	36 x Osram LED	36 x Osram LED	64 x Osram LED
Lumens (theor. / tested)	6600 lm / 6020 lm	6700 lm / 6050 lm	10100 lm / 9240 lm
Color temperature	5000 K	5000 K	5000 K
IP rating	IP68	IP68	IP68
Cable / connection	Integrated DT-plug downward	Integrated DT-plug downward	Integrated DT-plug downward
Size (W x H x D)	109 x 101 x 45 mm	101 x 101 x 45 mm	112 x 112 x 54 mm
Approvals	R10	R10	R10

1603-300232

1603-300233

1603-300234